Schottky Barrier Rectifier


STR15V40SP THRU STR15V200SP 40 to 200 V 15.0A

RoHS COMPLIANT

DO-27(DO-201AD)

Features And Mechanical Data

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction ,majority carrier conduction
- Guard ring for over voltage protection
- Low power loss ,high efficiency
- High current capability ,Low forward voltage drop High surge capability
- For use in low voltage ,high frequency inverters, free wheeling ,and polarity protection applications
- High temperature soldering:260℃ MAX at 10 seconds, per JESD 22-B106 or MIL-STD-750,method 2026
- Case: JEDEC D0-27(D0-201AD) molded plastic body



Dimensions in inches and (millimeters)

苏州福摩斯

Maximum Ratings and Electrical Characteristics

Ratings at 25℃ ambient temperature unless otherwise specified. Single phase, half wave, 60HZ, resistive or inductive load. For capacitive load, derate current by 20%.

	Symbols	STR 15V40 SP	STR 15V45 SP	STR 15V60 SP	STR 15V80 SP	STR 15V100 SP	STR 15V120 SP	STR 15V150 SP	STR 15V200 SP	Units
Device Marking		15V40SP S15V40	15V45SP S15V45	15V60SP S15V60	15V80SP S15V80	15V100SP S15V100	15V120SP S15V120	15V150SP S15V150	15V200SP S15V200	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	40	45	60	80	100	120	150	200	Volts
Maximum RMS Voltage	V_{RMS}	28	31.5	42	56	70	84	105	140	Volts
Maximum DC Blocking Voltage	V_{DC}	40	45	60	80	100	120	150	200	Volts
Maximum Average Forward Rectified Current. Lead Length @Ta(Fig 1)	$I_{(AV)}$	15.0								Amp
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method) (Rating of per diode)	I_{FSM}	200								Amp
Maximum instantaneous forward voltage at $I_{(AV)}$	V_F	0.38		0.42	0.67			0.72	0.78	Volts
Maximum DC reverse current at rated DC blocking voltage per T_j=25℃	I_R	0.2			0.1					mA
T_j=100℃		50			10					
Typical Thermal Resistance Note (1)	$R_{\theta JA}$	75								℃/W
Note (2)		33								
Junction Temperature	T_J	-65 to +150								℃
Storage Temperature Range	T_{STG}	-65 to +150								℃

Note 1. FR-4 PCB, 2 oz Copper. Minimum recommended pad layout

Note 2. Polymide PCB, 2 oz Copper. Cathode pad dimensions 18.8x14.4mm , Anode pad dimensions- (5.6x14.4mm)

RATINGS AND CHARACTERISTIV CURVES

RoHS COMPLIANT




Fig. 1 Forward Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Peak Forward Surge Current




Fig.4-Typical Forward Characteristics