


Features

- Glass passivated die construction
- Low forward voltage drop
- High current capability
- High surge current capability
- Designed for surface mount application
- Plastic material-UL flammability 94V.0

Mechanical Data

- Case: SOPA-4, molded plastic ABS
- Terminals: plated leads solderable per MIL-STD-202, Method 208
- Polarity: as marked on case
- Mounting position: Any
- Marking: type number



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single Phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

TYPE NUMBER	SYMBOL	HABS22	HABS24	HABS26	HABS28	HABS210	UNITS
Peak Repetitive Reverse Voltage	V_{RRM}	200	400	600	800	1000	V
Working Peak Reverse Voltage	V_{RWM}						
DC Blocking Voltage	V_{DC}						
RMS Reverse Voltage	V_{RMS}	140	280	420	560	700	V
Average Rectified Output Current @T _c =100°C	IF(AV)	2.0					A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	IFSM	60					A
Rating for fusing (t<8.3ms)	I ² t	14.94					A ² s
Forward Voltage per element @IF=2.0A	V _{FM}	1.0	1.3	1.7			V
Maximum Reverse Recovery Time (Note 1)	T _{rr}	50		75			ns
Peak Reverse Current @T _A =25°C At Rated DC Blocking Voltage @T _A =125 °C	I _R	5.0 500					uA
Typical Thermal Resistance per leg	R _{θJA}	62.5					°C/W
	R _{θJL}	25					
Operating and Storage Temperature Range	T _J , T _{STG}	-55to+150					°C

Note: 1.Reverse Recovery Test Conditions: $I_F = 0.5\text{A}$, $I_R = 1.0\text{A}$, $IRR = 0.25\text{A}$.

RATINGS AND CHARACTERISTIC CURVES

FIG.1 FORWARD CURRENT DERATING CURVE




FIG.2 TYPICAL FORWARD CHARACTERISTICS




FIG.3 MAXIMUM NON-REPETITIVE




FIG. 4-TYPICAL REVERSE LEAKAGE CHARACTERISTICS

